

Safety Data Sheet

FOR INDUSTRIAL USE ONLY

FLEXTEMP

Section 1. Product and company identification

Product Name:	Eastman(TM) DMAA
SDS Number:	150000063081
Product Type:	Solvent
Product Use:	Industrial
Manufacturer	Polynt Composites USA, Inc. 99 East Cottage Avenue Carpentersville IL 60110 E-Mail: MSDS@pccrusa.com
Supplier Telephone	FlexKrete Technologies, 881 N. Louisiana Dr., Celina, TX 75009 972-964-8707
	For Emergency Transportation Information CHEMTREC US Domestic (800) 424-9300 CHEMTREC International (703) 527-3887 For additional health and safety or regulatory information, call 1 847-836-3627.

Section 2. Hazard(s) identification

EMERGENCY OVERVIEW: INHALATION CAUSES HEADACHES, DIZZINESS, DROWSINESS, AND NAUSEA AND MAY LEAD TO UNCONSIOUSNESS. IN USE, MAY FORM FLAMMABLE/EXPLOSIVE VAPOUR-AIR MIXTURE. IRRITATING TO EYES, RESPIRATORY SYSTEM AND SKIN.

GHS Classification

Symbol(s) of Product

No GHS Symbols Exist

Signal Word

No Signal Word has been assigned

Section 3. Composition/Information on ingredients					
<u>Chemical Name</u> Butanamide, N,N-dimethyl-3-oxo-	<u>CAS-No.</u> 2044-64-6	<u>Wt. %</u> 20-60	GHS Symbols No Information	GHS Statements No Information	
The text for GHS Hazard Statements shown above (if any) Propylene Glycol Iron (1+)	is given in the "C 200-338-0 pre-registered	0ther inform 10-40 .25	None Xn,R22,Xn,R48/22,Xi		
chloro dimethyl-9.9-dihyd roxy-3methyl-2,4-di-(2-p yridyl-kN)-7-12-pyridinyl-kN)methyl-3,7-diazabicy clo 3.3.1 nonane-1-5-dicar boxylate-kN3,kN7 chloride 1-478945-46-9	Page 1 /	6	R43, R52/53	Skin Sens, 1; H317 STOT RE 2; H373 Aquatic Chronic 3; H412	

Section 4. First-aid measures



FIRST AID - EYE CONTACT: Hold eyelids apart and immediately flush with plenty of water for 15 minutes. Seek medical advice. Remove contact lenses.

FIRST AID - INGESTION: Rinse mouth with water. Never give anything by mouth to an unconscious person. Obtain medical attention. If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, administer CPR until help arrives or the victim starts to breathe on his own. If breathing is difficult, give oxygen. Seek medical attention immediately.

FIRST AID - SKIN CONTACT: Immediately flush with water for at least 15 minutes. Remove contaminated clothing. Seek medical attention immediately. Wash thoroughly after handling.

Section 5. Fire-fighting measures

Extinguishing Media:

SuitableDry Chemical, C02, Water Fog/Mist, FoamNot suitableWater Jet

SPECIAL FIREFIGHTING PROCEDURES: Wear full protective gear & SCBA.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Container may rupture on heating.

ENVIRONMENTAL MEASURES: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Use personal protective equipment. Prevent further leakage or spillage if safe to do so. Try to prevent the material from entering drains or water courses. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

PRECAUTIONARY MEASURES: Put on appropriate personal protective equipment (see Section 8). Do not touch or walk through spilled material. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains, and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil, or air).

Section 7. Handling and storage



HANDLING: Avoid breathing vapor and contact with eyes, skin and clothing. Do not leave containers open. Avoid repeated or prolonged contact with skin. Empty containers retain product residue. Observe all safety precautions. Do not reuse container.

STORAGE: Keep away from oxidizers, heat or flames. Keep in cool, dry, ventilated storage and in closed containers. Store away from all ignition sources. Ground all containers during transfer. Store in a cool, dry place. Keep container close. Protect from damage. Store away from flame and ignition sources. Keep all containers tightly closed when not in use. Store out of direct sunlight and on an impermeable floor. Do not store with incompatible materials. Store in upright position only.

HYGIENIC PRACTICES: General industrial hygiene practice. Wash hands before eating, drinking, or smoking.

WORK PRACTICES: Put on appropriate personal protective equipment. Wash hands after handling chemicals and before eating, drinking, or smoking. Read and understand entire SDS before handling chemical.

SPECIAL HANDLING PROCEDURES: Put on appropriate personal protective equipment. Eating, drinking, and smoking should be prohibited in areas where this material is handled, stored, and processed. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use.

Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Follow US NFPA 30, "Flammable and Combustible Liquids Code", or other national, state and local codes on safe handling of flammable liquids. Train workers in the recognition and prevention of hazards associated with the storage, handling, and transfer of flammable liquids in the plant. Empty containers retain product residue and can be hazardous.

Ingredients with Occupational Exposure Limits

Chemical Name	ACGIH TLV-TWA	ACGIH-TLV STEL	<u>OSHA PEL-TWA</u>	OSHA CEILING
Butanamide, N,N-dimethyl-3-oxo-	N.E.	N.E.	N.E.	N.E.

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

Personal Protection

RESPIRATORY PROTECTION: Use a properly-fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.



SKIN PROTECTION: Chemical resistant gloves and chemical goggles should be used to prevent skin and eye contact. Impervious gloves.



EYE PROTECTION: Safety glasses with side-shields. Avoid contact with eyes.



OTHER PROTECTIVE EQUIPMENT: Use good hygiene practices. Wash face and hands before eating, drinking, and smoking. Eye wash and safety showers should be readily available.

HYGIENIC PRACTICES: General industrial hygiene practice. Wash hands before eating, drinking, or smoking.

Section 9. Physical and chemical properties

Color:	Yellow	Physical State:	Liquid
Odor:	Ammonia	Odor Threshold:	Not Available
Density, g/cm3:	1.060	pH:	Not Available
Freeze Point, °C:	Not Available	Viscosity:	Not Available
Solubility in Water:	Complete	Partition Coefficient, n-octanol/ water:	Not Available
Decompostion Temp., °C:	Not Available	Flash Point, °C / F°	122 / 252
Boiling Range, °C:	999	Explosive Limits, vol%:	Not Available
Vapor Pressure:	Not Available	Auto-ignition Temp., °C:	Not Available

(See "Other information" Section for abbreviation legend)

Section 10. Stability and reactivity

STABILITY: This material is stable under normal storage and handling conditions.

CONDITIONS TO AVOID: High temperatures, sparks, open flame, and all other sources of ignition. Avoid heat, sparks, flames and other ignition sources.

INCOMPATIBILITY: Keep away from strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon oxides

Section 11. Toxicological information



Practical Experiences

EFFECT OF OVEREXPOSURE - EYE CONTACT: May cause irritation, discomfort, reddening and tearing.

EFFECT OF OVEREXPOSURE - INGESTION: May cause irritation of the respiratory tract and CNS effects such as dizziness, Page 3 / 6

headaches, nausea and narcosis.

EFFECT OF OVEREXPOSURE - INHALATION: Inhalation of high concentrations may cause headache, nausea, and dizziness.

EFFECT OF OVEREXPOSURE - SKIN CONTACT: Prolonged contact may cause irritation and/or redness.

EFFECT OF OVEREXPOSURE - CHRONIC HAZARDS: No Information

CARCINOGENICITY: No Information

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Contact

Acute Toxicity Values The acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.Name according to EECOral LD50Dermal LD50Vapor LC50

No hazardous items exist

N.I. - No Information

Section 12. Ecological information

ECOLOGICAL INFORMATION: Ecological evaluation of this material has not been performed; however, do not allow the product to be released to the environment without governmental approval/permits. Discharge into the environment must be avoided.

Section 13. Disposal considerations



DISPOSAL METHOD: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should always comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains, and sewers.

Section 14. Transport information

SPECIAL TRANSPORT PRECAUTIONS: Not regulated by D.O.T. if in a container of 119 gallon capacity or less.

International transport regulations

Regulatory Information:	UN/NA Number	Proper Shipping Name	Classes/ *PG	Reportable Quantity (RQ)
CFR	Not regulated	Not regulated	Class 3 No Information	No Information
IMO/IMDG	Not regulated	Not regulated	Class 3 No Information	No Information
IATA (Cargo)	Not regulated	Not regulated	Class 3 No Information	No Information

Section 15. Regulatory information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA components exist in this product.

U.S. State Regulations: NEW JERSEY RIGHT-TO-KNOW:

The following hazardous materials are listed.

No NJ Right-To-Know components exist in this product.

PENNSYLVANIA RIGHT-TO-KNOW

The following hazardous ingredients are present:

No PA Right-To-Know components exist in this product.

U.S. State Regulations: MASSACHUSETTS RIGHT-TO-KNOW:

The following hazardous materials are listed.

No MA Right-To-Know components exist in this product.

CALIFORNIA PROPOSITION 65 CARCINOGENS

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

No Proposition 65 Carcinogens exist in this product.

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

No Proposition 65 Reproductive Toxins exist in this product.

International Regulations

CANADIAN WHMIS:

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

WHMIS Class: No Information

Chemical Inventories	Australia inventory (AICS)	All components are listed or exempted	
	Canada inventory (DSL)	All components are listed or exempted	
	Japan Inventory (ENCSC)	All components are listed or exempted	
	China Inventory (IECSC)	All components are listed or exempted	
	Korea Inventory (KECI)	All components are listed or exempted	
	New Zealand (NZIoC)	All components are listed or exempted	
	Philippines (PICCS)	All components are listed or exempted	
	United States Inventory (TSCA 8b)	All components are listed or exempted	
Section 16. Other i	nformation, including date of	preparation of the last revision	
Revision Date:	7/16/2015	Supercedes Date:	Now SDS

					Supercedes Da	ale.	New SD
evision:							
•	Regulatory L	epartment					
Flammability:	1	Reactivity:	0	Personal Protection:	N.I.	Chronic Rating:	N.I.
	oduced by: s:	oduced by: Regulatory D	s:	s:	s:	s:	boduced by: Regulatory Department s: Elammability: 1 Reactivity: 0 Personal N L Chronic Bating:

Icons for GHS Pictograms shown in Section 3 describing each ingredient:

No GHS Pictograms exist for Section 3

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

The information provided herein was believed by Polynt Composites USA, Inc. to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product and to determine the suitability of the product for its intended use. All products supplied by Polynt Composites USA, Inc. are subject to Polynt Composites USA, Inc terms and conditions of sale. Polynt Composites USA, Inc. MAKES NO WARRANTY, EXPRESSED OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY Polynt Composites USA, Inc, except that the product shall conform to Polynt Composites USA, Inc. specifications. Nothing contained herein constitutes an offer for the sale of any product.